

## Push Trolley KITO HD3C Handycat painted

---

### Product information

NO PICTURE

- Revolutionary stable 3 bolt system, for large beam range
- Material traceability for all load carrying parts
- Suitable for all beam types
- Easy to mount principle by turning the spindle
- Easy click in system for the hoists
- Smart securing system preventing the trolley to loose beam adjustment
- Wheel break supports, hand chain guide with anti-drop device
- Trolley wheels with lifetime lubricated bearing
- Suspension ring, high grade steel
- Also available in Explosion Protected Execution (ATEX)

... [Read more](#)

---

**Marking:** According to standard

**Finish:** Painted

**Standard:** EN 13157

## Push Trolley KITO HD3C Handycat painted

### Technical data

Part code	WLL (metric tonnes)	Beam width	A in	B in	C in	D, in	D1mm in	E in	F in	G, in	H, in	L in	Mmm in	Nmm in	N1 in	N2 in	Omm in	Rmm in	S in	Weight lb
502500101800370	1	55-180	2.36	2.95	0.71	1.77	4.72	0.79	2.36	1.14	7.44	7.48	2.56	3.54	6.54	8.98	3.94	3.9	0.87	15.43
502500103050370	1	180-305	2.36	2.95	0.71	1.77	4.72	0.79	2.36	1.14	7.44	7.48	2.56	3.54	0.04	13.74	3.94	3.9	0.87	17.64
502500201800370	2	74-180	3.15	3.94	0.87	2.17	5.91	1.06	2.95	1.38	7.76	10.04	2.56	3.54	6.73	9.33	3.94	4.84	0.98	30.86
502500203050370	2	180-305	3.15	3.94	0.87	2.17	5.91	1.06	2.95	1.38	7.76	10.04	2.56	3.54	0.08	14.09	3.94	4.84	0.98	33.07
502500321800370	3.2	90-180	3.94	4.72	0.98	2.64	7.76	1.38	3.74	1.57	8.27	11.81	2.76	3.74	6.93	9.65	3.94	5.67	1.26	50.71
502500323050370	3.2	180-305	3.94	4.72	0.98	2.64	7.76	1.38	3.74	1.57	8.27	11.81	2.76	3.74	9.29	14.41	3.94	5.67	1.26	52.91
502500501800370	5	106-180	4.92	5.91	1.18	3.54	9.06	1.57	4.53	2.36	9.25	14.76	3.94	5.12	7.4	10.2	5.31	6.85	1.5	85.98
502500503050370	5	180-305	4.92	5.91	1.18	3.54	9.06	1.57	4.53	2.36	9.25	14.76	3.94	5.12	9.76	14.96	5.31	6.85	1.5	88.18