

Geared Trolley TSG KITO

Product information

General: Geared trolley with capacity from 0,125 tons up to 5 tons. The standard trolley includes rubber bumper, safety lug and suspender.

... [Read more](#)



Material: Pressed steel plate.

Marking: According to standard, CE-marked

Temperature range: -40°C up to +60°C (-20°C up to + 40°C for the use with a electric chain hoist)

Standard: EN 13157

Safety factor: 4:1

Geared Trolley TSG KITO

Technical data

Part code	WLL (metric) tonnes	Beam width in	Model	Chain length m
502600011630030	0.125	2.28-6.42	Standard	3
502600013050030	0.125	6.46-12.01	W30	3
502600031630030	0.25	2.28-6.42	Standard	3
502600033050030	0.25	6.46-12.01	W30	3
502600051630030	0.5	2.28-6.42	Standard	3
502600053050030	0.5	6.46-12.01	W30	3
502600101630030	1	2.28-6.42	Standard	3
502600103050030	1	6.46-12.01	W30	3
502600152040030	1.5	3.23-8.03	Standard	3
502600153050030	1.5	8.07-12.01	W30	3
502600202040030	2	3.23-8.03	Standard	3
502600203050030	2	8.07-12.01	W30	3
502600252040030	2.5	3.23-8.03	Standard	3
502600253050030	2.5	8.07-12.01	W30	3
502600302040030	3	3.23-8.03	Standard	3
502600303050030	3	8.07-12.01	W30	3
502600301530030	3	3.23-6.02	-	2.5
502600502040030	5	3.94-8.03	Standard	3.5
502600503050030	5	8.07-12.01	W30	3,5
502600752200030	7.5	5.91-8.66	Standard	3.5
502600753050030	7.5	8.7-12.01	W30	3,5
502601002200030	10	5.91-8.66	Standard	4
502601003050030	10	8.7-12.01	W30	4,0
502601502200030	15	5.91-8.66	Standard	4.5
502601503050030	15	8.7-12.01	W30	4.5
502602002200030	20	5.91-8.66	Standard	4.5
502602003050030	20	8.7-12.01	W30	4.5
502603001900030	30	7.48	Standard	4.5
502603003050030	30	7.52-12.01	W30	4.5