Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Fast Reeve Crane Blocks 2 sheave

Product information



General:
- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:
- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:
Inquiries for custom versions are welcome!

... *Read more*

© November 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group
Axel Johnson International

Fast Reeve Crane Blocks 2 sheave

Blueprint



© November 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Fast Reeve Crane Blocks 2 sheave

Technical data

Part code	WLL (metric) tonnes	Model	Rope Ø mm	Sheave dia. mm	Hook size	øD1 in	øD2 in	B in	O in	TA in	TB in	TLmm in	L in	T in	øZ in	Weight lb
6097FRB22514216E	16	FRB 225 .14 .2 .16 .E	14	260 / 255	6	10.24	8.86	23.94	2.32	13.58	7.09	34.76	43.43	1.1	1.26	231.49
6097FRB26014216E	16	FRB 260 .14 .2 .16 .E	14	300 / 260	6	11.81	10.24	27.28	2.32	15.75	6.5	38.5	45.98	1.1	1.26	275.58
6097FRB26016216E	16	FRB 260 .16 .2 .16 .E	16	300 / 260	6	11.81	10.24	27.28	2.32	15.75	6.5	38.5	45.98	1.1	1.26	275.58
6097FRB26014220E	20	FRB 260 .14 .2 .20 .E	14	300 / 260	8	11.81	10.24	29.45	2.72	15.75	6.5	40.67	43.43	1.1	1.26	286.6
6097FRB26016220E	20	FRB 260 .16 .2 .20 .E	16	300 / 260	8	11.81	10.24	29.45	2.72	16.54	6.5	40.67	47.76	1.1	1.26	286.6
6097FRB28516220E	20	FRB 285 .16 .2 .20 .E	16	365 / 285	8	14.37	11.22	30.63	2.72	16.54	6.5	42.44	48.66	1.1	1.26	352.74
6097FRB32016220E	20	FRB 320 .16 .2 .20 .E	16	365 / 320	8	14.37	12.6	30.24	2.72	17.72	7.09	43.35	48.46	1.1	1.26	352.74
6097FRB32016225E	25	FRB 320 .16 .2 .25 .E	16	365 / 320	8	14.37	12.6	30.04	2.72	17.72	5.12	43.15	52.48	1.1	1.26	451.95
6097FRB35519229E	29	FRB 355 .19 .2 .29 .E	19	410 / 355	8	16.14	13.98	33.39	2.72	19.69	8.86	46.97	54.84	1.38	1.46	584.23
6097FRB40019229E	29	FRB 400 .19 .2 .29 .E	19	460 / 400	8	18.11	15.75	34.37	2.72	22.44	9.45	49.33	55.04	1.38	1.46	804.69
6097FRB40022229E	29	FRB 400 .22 .2 .29 .E	22	460 / 400	8	18.11	15.75	34.37	2.72	22.44	9.45	49.33	61.89	1.57	1.69	804.69
6097FRB45022232E	32	FRB 450 .22 .2 .32 .E	22	515 / 450	10	20.28	17.72	39.49	2.99	23.62	9.84	55.75	65.16	1.57	1.69	1,069.24
6097FRB45022240E	40	FRB 450 .22 .2 .40 .E	22	515 / 450	12	20.28	17.72	42.28	3.31	23.62	13.11	58.54	65.55	1.57	1.69	1,300.73
6097FRB45024240E	40	FRB 450 .24 .2 .40 .E	24	515 / 450	12	20.28	17.72	42.28	3.31	23.62	13.11	58.54	66.5	1.77	2.05	1,300.73
6097FRB45026240E	40	FRB 450 .26 .2 .40 .E	26	515 / 450	12	20.28	17.72	42.28	3.31	23.62	13.11	58.94	66.5	1.77	2.05	1,300.73
6097FRB45024250E	50	FRB 450 .24 .2 .50 .E	22	515 / 450	16	20.28	17.72	42.28	3.82	23.62	14.29	58.94	65.94	1.77	2.05	1,499.14
6097FRB45026250E	50	FRB 450 .26 .2 .50 .E	26	515 / 450	16	20.28	17.72	42.28	3.82	23.62	14.29	58.94	72.76	1.77	2.05	1,499.14
6097FRB52824263E	63	FRB 528 .24 .2 .63 .E	24	595 / 528	16	23.43	20.79	47.32	3.82	27.95	15.08	65.2	72.76	1.77	2.05	2,204.62
6097FRB52826263E	63	FRB 528 .26 .2 .63 .E	26	595 / 528	16	23.43	20.79	47.32	3.82	27.95	15.08	65.2	76.61	1.77	2.05	2,204.62
6097FRB52828263E	63	FRB 528 .28 .2 .63 .E	28	595 / 528	16	23.43	20.79	47.36	3.82	27.95	15.08	66.18	77.6	1.97	2.32	2,204.62
6097FRB52826280E	80	FRB 528 .26 .2 .80 .E	26	595 / 528	20	23.43	20.79	50.08	4.33	27.95	16.22	68.35	74.13	1.77	2.05	2,347.93
6097FRB52828280E	80	FRB 528 .28 .2 .80 .E	28	595 / 528	20	23.43	20.79	50.12	4.33	27.95	16.22	68.94	83.35	1.97	2.32	2,347.93
6097FRB670282100E	100	FRB 670 .28 .2 .100 .E	28	760 / 670	20	29.92	26.38	52.44	4.33	34.25	18.98	74.69	83.54	1.97	2.32	4,938.36
6097FRB670322100E	100	FRB 670 .32 .2 .100 .E	32	760 / 670	20	29.92	26.38	52.44	4.33	34.25	18.98	74.69	122.91	2.36	2.6	4,938.36

© November 2026 - All Rights Reserved