

Fast Reeve Crane Blocks 4 sheave

Product information



General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.


Important:

Inquiries for custom versions are welcome!

[... Read more](#)

Fast Reeve Crane Blocks 4 sheave

Blueprint



Fast Reeve Crane Blocks 4 sheave

Technical data

Part code	WLL (metric) tonnes	Model	Rope Ø mm	Sheave dia. mm	Hooksize	Ø D1 mm in	Ø D2 mm in	B in	Omm in	TA mm in	TBmm in	TLmm in	L in	T in	Ø Z mm in	Weight lb
6097FRB28516435E	35	FRB 285 .16 .4 .35 .E	16	320 / 285	12	12.6	11.22	29.65	3.31	16.54	11.5	41.46	46.1	1.1	1.26	606.27
6097FRB35519450E	50	FRB 355 .19 .4 .50 .E	19	410 / 355	12	16.14	13.98	37.76	3.31	19.69	14.29	48.39	53.03	1.38	1.46	1,102.31
6097FRB40022463E	63	FRB 400 .22 .4 .63 .E	22	460 / 400	16	18.11	15.75	40.87	3.82	22.44	13.78	52.48	57.68	1.57	1.69	1,190.5
6097FRB35519463E	63	FRB 355 .19 .4 .63 .E	19	410 / 355	16	16.14	13.98	40.87	3.82	19.69	13.5	51.5	56.69	1.38	1.46	1,256.64
6097FRB45022463E	63	FRB 450 .22 .4 .63 .E	22	510 / 450	16	20.28	17.72	40.87	3.82	23.62	15.75	57.01	62.2	1.57	1.69	1,653.47
6097FRB45024463E	63	FRB 450 .24 .4 .63 .E	24	510 / 450	16	20.28	17.72	40.87	3.82	23.62	15.75	57.01	62.2	1.77	2.05	1,653.47
6097FRB45024480E	80	FRB 450 .24 .4 .80 .E	24	510 / 450	20	20.28	17.72	46.57	4.33	23.62	20.75	61.73	67.64	1.77	2.05	2,204.62
6097FRB45026480E	80	FRB 450 .26 .4 .80 .E	26	510 / 450	20	20.28	17.72	46.57	4.33	23.62	20.75	61.73	67.64	1.57	2.05	2,204.62
6097FRB52824480E	80	FRB 528 .24 .4 .80 .E	24	590 / 528	20	23.43	20.79	50.08	4.33	27.95	20.75	68.35	74.25	1.77	2.05	2,204.62
6097FRB52826480E	80	FRB 528 .26 .4 .80 .E	26	590 / 528	20	23.43	20.79	50.08	4.33	27.95	20.75	68.35	74.25	1.77	2.05	2,204.62
6097FRB52828480E	80	FRB 528 .28 .4 .80 .E	28	590 / 528	20	23.43	20.79	50.12	4.33	27.95	18.58	65.79	71.69	1.57	2.32	2,799.87
6097FRB528264100E	100	FRB 528 .26 .4 .100 .E	26	590 / 528	25	23.43	20.79	50.71	5.2	27.95	18.58	68.62	75.31	1.57	2.05	2,799.87
6097FRB528284100E	100	FRB 528 .28 .4 .100 .E	28	590 / 528	25	23.43	20.79	50.71	5.2	27.95	18.58	69.02	75.71	1.57	2.32	2,799.87
6097FRB575284125E	125	FRB 575 .28 .4 .125 .E	28	650 / 575	32	25.59	22.64	55.63	5.39	30.31	17.4	74.53	82.01	1.57	2.32	2,998.29
6097FRB670284160E	160	FRB 670 .28 .4 .160 .E	28	760 / 670	40	29.92	26.38	63.62	6.57	34.25	26.06	85.87	94.21	1.97	2.32	6,944.57
6097FRB670324160E	160	FRB 670 .32 .4 .160 .E	32	760 / 670	40	29.92	26.38	63.62	6.57	34.25	26.06	85.87	94.21	2.36	2.6	6,944.57