

Fast Reeve Crane Blocks 5 sheave

Product information



General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.


Important:

Inquiries for custom versions are welcome!

[... Read more](#)

Fast Reeve Crane Blocks 5 sheave

Blueprint



Technical data

Part code	WLL (metric) tonnes	Model	Rope Ø mm	Sheave dia. mm	Hooksize	B in	L in	Omm in	T in	TA mm in	TBmm in	TLmm in	Ø D1 mm in	Ø D2 mm in	Ø Z mm in	Weight lb
6097FRB35516550E	50	FRB 355 .16 .5 .50 .E	16	410 / 355	12	37.76	52.83	3.31	1.1	19.69	15.04	48.19	16.14	13.98	1.26	1,102.31
6097FRB36019563E	63	FRB 360 .19 .5 .63 .E	19	420 / 360	16	38.31	54.13	3.82	1.18	20.08	16.61	48.94	16.54	14.17	1.46	1,322.77
6097FRB40019563E	63	FRB 400 .19 .5 .63 .E	19	460 / 400	16	41.26	59.84	3.82	1.18	22.44	17.01	54.65	18.11	15.75	1.46	1,653.47
6097FRB45022580E	80	FRB 450 .22 .5 .80 .E	22	515 / 450	20	46.77	68.11	4.33	1.18	23.62	17.2	62.2	20.28	17.72	1.69	1,796.77
6097FRB45024580E	80	FRB 450 .24 .5 .80 .E	24	515 / 450	20	46.77	68.11	4.33	1.57	23.62	17.2	62.2	20.28	17.72	2.05	1,796.77
6097FRB36019580E	80	FRB 360 .19 .5 .80 .E	19	420 / 360	20	42.6	59.13	4.33	1.18	20.08	18.98	53.23	16.54	14.17	1.46	1,807.79
6097FRB40019580E	80	FRB 400 .19 .5 .80 .E	19	460 / 400	20	45.16	62.87	4.33	1.18	22.44	19.96	56.97	18.11	15.75	1.46	1,807.79
6097FRB450245100E	100	FRB 450 .24 .5 .100 .E	24	515 / 450	25	49.72	69.61	5.2	1.77	23.62	16.42	62.91	20.28	17.72	2.05	2,006.21
6097FRB450265100EA	100	FRB 450 .26 .5 .100 .E .A	26	515 / 450	25	49.72	69.61	5.2	1.57	23.62	16.42	62.91	20.28	17.72	2.05	2,006.21
6097FRB450265100EB	100	FRB 450 .26 .5 .100 .E .B	26	515 / 450	25	49.72	69.61	5.2	1.57	23.62	19.96	62.91	20.28	17.72	2.05	2,513.27
6097FRB528245125E	125	FRB 528 .24 .5 .125 .E	24	595 / 528	32	52.48	75.31	5.39	1.77	27.95	24.49	67.83	23.43	20.79	2.05	4,012.42
6097FRB528265125E	125	FRB 528 .26 .5 .125 .E	26	595 / 528	32	52.48	75.31	5.39	1.77	27.95	24.49	67.83	23.43	20.79	2.05	4,012.42
6097FRB528285125E	125	FRB 528 .28 .5 .125 .E	28	595 / 528	32	52.48	75.31	5.39	1.97	27.95	24.49	67.83	23.43	20.79	2.32	4,012.42
6097FRB528265150E	150	FRB 528 .26 .5 .150 .E	26	595 / 528	40	52.48	76.18	6.57	1.97	27.95	23.7	67.83	23.43	20.79	2.05	4,012.42

Fast Reeve Crane Blocks 5 sheave

Technical data

Part code	WLL (metric) tonnes	Model	Rope Ø mm	Sheave dia. mm	Hooksize	B in	L in	Omm in	T in	TA mm in	TBmm in	TLmm in	Ø D1 mm in	Ø D2 mm in	Ø Z mm in	Weight lb
6097FRB528285150E	150	FRB 528 .28 .5 .150 .E	28	595 / 528	40	52.48	76.3	6.57	1.97	27.95	24.49	67.95	23.43	20.79	2.32	4,012.42
6097FRB575285150E	150	FRB 575 .28 .5 .150 .E	28	650 / 575	40	54.45	79.33	6.57	1.97	30.31	22.52	70.98	25.59	22.64	2.05	4,012.42
6097FRB528285160E	160	FRB 528 .28 .5 .160 .E	28	595 / 528	40	59.13	86.26	6.57	1.97	27.95	26.06	77.91	23.43	20.79	2.32	5,004.5
6097FRB575285160E	160	FRB 575 .28 .5 .160 .E	28	650 / 575	40	62.64	87.52	6.57	1.97	30.31	23.31	79.17	25.59	22.64	2.32	5,004.5
6097FRB670285200E	200	FRB 670 .28 .5 .200 .E	28	760 / 670	50	67.56	96.14	7.4	1.97	34.25	30.79	86.85	29.92	26.38	2.32	7,848.46
6097FRB670325200E	200	FRB 670 .32 .5 .200 .E	32	760 / 670	50	67.56	96.14	7.4	2.36	34.25	30.79	86.85	29.92	26.38	2.6	7,848.46