

Samson wire rope blocks 3 sheave

Product information



General:

- Up to 30 ton blocks standard supplied with swivel oval eye.
- Over 30 ton blocks standard supplied with swivel stud eye.
- Blocks can be supplied with swivel hook, swivel stud eye or swivel jaw on request.
- Standard supplied with bronze bearings. Other bearings available on request.
- Groove in sheave may be adjusted to other wire rope diameters on request.
- Blocks can be supplied with becket on request.

... [Read more](#)


Temperature range: -40°C / +80°C

Note: WLL= Working Load Limit on head fitting

Safety factor: 4:1

Samson wire rope blocks 3 sheave

Blueprint



Technical data

| Part code | WLL (metric) tonnes | Rope Ø mm | No of Sheaves | Weight lb |
|--------------|------------------------|--------------|---------------|--------------|
| 424100200330 | 2 | 10 | 3 | 19.84 |
| 424100400330 | 4 | 12 | 3 | 37.48 |
| 424100600330 | 6 | 14 | 3 | 61.73 |
| 424100800330 | 8 | 18 | 3 | 101.41 |
| 424101000330 | 10 | 20 | 3 | 152.12 |
| 424101200330 | 12 | 22 | 3 | 218.26 |
| 424101600330 | 16 | 24 | 3 | 264.55 |
| 424101600335 | 16 | 24 | 3 | 346.13 |
| 424102000335 | 20 | 24 | 3 | 315.26 |
| 424102000330 | 20 | 24 | 3 | 405.65 |
| 424102500330 | 25 | 24 | 3 | 374.79 |
| 424102500335 | 25 | 24 | 3 | 436.52 |
| 424102500336 | 25 | 28 | 3 | 485.02 |
| 424103000330 | 30 | 28 | 3 | 473.99 |
| 424103000335 | 30 | 28 | 3 | 562.18 |
| 424104000330 | 40 | 28 | 3 | 551.16 |
| 424104000335 | 40 | 28 | 3 | 650.36 |
| 424105000330 | 50 | 28 | 3 | 738.55 |