

Single Sheave Crane Blocks

Product information




General:

- Standard fitted with becket, cylindrical roller bearing and reeving guide.
- Standard fitted with Crosby type of swivel only hook (319AN style), including safety latch and split pin.
- Standard painted yellow (no striping).
- This crane block may be used with 2 lines only as well.
- Sheaves may be adjustud for other wire rope diameters.
- Becket suitable for connecting Open Wedge Socket for indicated wire rope.
- Becket can not be adjusted.

... [Read more](#)

Single Sheave Crane Blocks

Blueprint



Technical data

Part code	WLL (metric) tonnes	Rope Ø mm	Sheave dia. mm	øD1 in	øD2 in	B in	Omm in	S in	TA mm in	TBmm in	TLmm in	T in	øZ in	Weight lb
6097HB2101115E	5	11	250/210	9.84	8.27	13.7	1.34	1.18	12.6	4.06	20.59	0.79	1.06	90.39
6097HB2201315E	5	13	260/221	10.24	8.7	13.9	1.34	1.18	13.9	4.29	20.67	0.87	1.06	147.71
6097HB2201418E	8	14	260/218	10.24	8.58	15.35	1.69	1.38	12.99	4.76	22.48	1.1	1.26	176.37
6097HB2551318E	8	13	300/255	11.81	10.04	16.77	1.69	1.18	14.57	3.98	24.45	0.87	1.06	196.21
6097HB2551618E	8	16	300/252	11.81	9.92	16.54	1.69	1.38	14.57	4.37	24.45	1.1	1.26	207.23
6097HB25516110E	10	16	300/252	11.81	9.92	18.07	2.05	1.38	14.57	5	25.94	1.1	1.26	200.62
6097HB22014110E	10	14	260/218	10.24	8.58	16.89	2.05	1.38	12.99	5.39	23.98	1.1	1.26	205.03
6097HB30516110E	10	16	350/305	13.78	12.01	19.65	2.05	1.38	17.13	4.21	29.09	1.1	1.3	249.12
6097HB34518112E	12	18	400/345	15.75	13.58	21.93	2.24	1.77	19.69	4.92	32.76	1.38	1.46	357.15
6097HB39020116E	16	20	450/390	17.72	15.35	23.31	2.24	1.97	21.65	5.16	36.1	1.38	1.69	454.15
6097HB43022120E	20	22	500/430	19.69	16.93	23.31	2.99	1.97	23.62	5.83	40.63	1.57	1.69	626.11