

Standard Reeve Crane Blocks 1 Sheave

Product information



General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.


Important:

Inquiries for custom versions are welcome!

... [Read more](#)

Standard Reeve Crane Blocks 1 Sheave

Blueprint



Technical data

Part code	WLL (metric) tonnes	Model	Rope Ø mm	Sheave dia. mm	Hook size	øD1 in	øD2 in	B in	Omm in	TA mm in	TBmm in	TLmm in	L in	T in	øZ in	Weight lb
6097SRB225141125E	12.5	SRB 225 .14 .1 .12,5 .E	14	260 / 255	5	10.24	8.86	20.59	2.17	1.38	6.69	31.06	35.94	1.1	1.26	165.35
6097SRB260141125E	12.5	SRB 260 .14 .1 .12,5 .E	14	300 / 260	5	11.81	10.24	21.57	2.17	15.75	7.28	36.73	25.51	1.1	1.26	242.51
6097SRB260161125E	12.5	SRB 260 .16 .1 .12,5 .E	16	300 / 260	5	11.81	10.24	21.57	2.17	15.75	7.28	36.73	37.32	1.1	1.26	242.51
6097SRB22514116E	16	SRB 225 .14 .1 .16 .E	14	260 / 255	5	10.24	8.86	21.57	2.17	13.58	7.09	36.34	36.93	1.1	1.26	220.46
6097SRB26016116E	16	SRB 260 .16 .1 .16 .E	16	300 / 260	5	11.81	10.24	21.57	2.17	15.75	7.68	36.73	37.32	1.1	1.26	242.51
6097SRB28516116E	16	SRB 285 .16 .1 .16 .E	16	320 / 280	6	12.6	11.02	23.94	2.24	16.54	6.5	35.75	40.67	1.1	1.26	352.74
6097SRB32016116E	16	SRB 320 .16 .1 .16 .E	16	365 / 320	6	14.37	12.6	24.72	2.32	17.72	8.07	37.44	42.36	1.1	1.26	352.74
6097SRB32019116E	16	SRB 320 .19 .1 .16 .E	19	365 / 320	6	14.37	12.6	24.72	2.32	17.72	8.07	37.44	42.56	1.38	1.46	352.74
6097SRB35516116EA	16	SRB 355 .16 .1 .16 .E .A	16	410 / 355	6	16.14	13.98	26.3	2.32	19.69	7.68	39.88	44.8	1.1	1.26	396.83
6097SRB35519116E	16	SRB 355 .19 .1 .16 .E	19	410 / 355	6	16.14	13.98	26.3	2.32	19.69	7.68	39.88	44.8	1.1	1.26	396.83
6097SRB35519120E	20	SRB 355 .19 .1 .20 .E	19	410 / 355	8	16.14	13.98	28.07	2.99	19.69	8.86	41.46	47.4	1.38	1.46	496.04
6097SRB40022129E	29	SRB 400 .22 .1 .29 .E	22	460 / 400	8	18.11	15.75	29.25	2.72	22.44	9.45	44.41	50.12	1.57	1.69	639.34
6097SRB45024132EA	32	SRB 450 .24 .1 .32 .E .A	24	515 / 450	10	20.28	17.72	32.8	2.99	23.62	13.78	49.45	55.98	1.77	2.05	1,003.1
6097SRB45026132EA	32	SRB 450 .26 .1 .32 .E .A	26	515 / 450	10	20.28	17.72	32.8	2.99	23.62	13.78	49.45	55.98	1.77	2.05	1,003.1
6097SRB45024132EB	32	SRB 450 .24 .1 .32 .E .B	24	515 / 450	10	20.28	17.72	32.8	2.99	23.62	16.14	49.45	55.98	1.77	2.05	1,300.73
6097SRB45026132EB	32	SRB 450 .26 .1 .32 .E .B	26	515 / 450	10	20.28	17.72	32.8	2.99	23.62	16.14	49.45	55.98	1.77	2.05	1,300.73
6097SRB45024140EB	40	SRB 450 .24 .1 .40 .E .B	24	515 / 450	12	20.28	17.72	42.28	3.31	23.62	16.14	58.54	65.55	1.77	2.05	1,300.73

Standard Reeve Crane Blocks 1 Sheave

Technical data

Part code	WLL (metric) tonnes	Model	Rope Ø mm	Sheave dia. mm	Hook size	øD1 in	øD2 in	B in	Omm in	TA mm in	TBmm in	TLmm in	L in	T in	øZ in	Weight lb
6097SRB45026140E	40	SRB 450 .26 .1 .40 .E	26	515 / 450	12	20.28	17.72	36.14	3.31	23.82	12.72	52.68	59.69	1.77	2.05	1,300.73
6097SRB52824150E	50	SRB 528 .24 .1 .50 .E	24	596 / 528	16	23.46	20.79	36.77	3.82	27.95	13.9	55.59	63.15	1.77	2.05	1,598.35
6097SRB52826150E	50	SRB 528 .26 .1 .50 .E	26	596 / 528	16	23.46	20.79	36.77	3.82	27.95	13.9	55.59	63.15	1.77	2.05	1,598.35
6097SRB52828150E	50	SRB 528 .28 .1 .50 .E	28	595 / 528	16	23.43	20.79	36.77	3.82	29.13	13.9	55.59	63.54	1.97	2.32	1,598.35
6097SRB57528150E	50	SRB 575 .28 .1 .50 .E	28	650 / 575	16	25.59	22.64	37.72	3.82	30.31	13.11	57.44	65.39	1.97	2.32	2,050.3
6097SRB63032163E	63	SRB 630 .32 .1 .63 .E	32	720 / 630	16	28.35	24.8	38.78	3.82	32.48	13.9	59.88	68.03	2.36	2.6	2,204.62
6097SRB67028163E	63	SRB 670 .28 .1 .63 .E	28	760 / 670	16	29.92	26.38	46.18	3.82	34.25	18.62	68.43	76.38	1.97	2.32	3,968.32
6097SRB67032163E	63	SRB 670 .32 .1 .63 .E	32	760 / 670	16	29.92	26.38	46.18	3.82	34.25	18.62	68.43	76.38	2.36	2.6	3,968.32