

Standard Reeve Crane Blocks 4 sheaves

Product information



General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

... [Read more](#)

Standard Reeve Crane Blocks 4 sheaves

Technical data

Part code	WLL (metric) tonnes	Model	Rope Ø mm	Hooksize	Weight lb
6097SRB28516435E	35	SRB 285 .16 .4 .35 .E	16	10	573.2
6097SRB35519450E	50	SRB 355 .19 .4 .50 .E	19	16	1,047.2
6097SRB40022463E	63	SRB 400 .22 .4 .63 .E	22	16	1,157.43
6097SRB45022463E	63	SRB 450 .22 .4 .63 .E	22	16	1,598.35
6097SRB45024480E	80	SRB 450 .24 .4 .80 .E	24	20	2,116.44
6097SRB45026480E	80	SRB 450 .26 .4 .80 .E	26	20	2,116.44
6097SRB528264100E	100	SRB 528 .26 .4 .100 .E	26	25	2,755.78
6097SRB528284100E	100	SRB 528 .28 .4 .100 .E	28	25	2,755.78
6097SRB670284160E	160	SRB 670 .28 .4 .160 .E	28	40	6,944.57
6097SRB670324160E	160	SRB 670 .32 .4 .160 .E	32	40	6,944.57