



Standard Reeve Crane Blocks 5 sheaves

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

Part code	WLL (metric) tonnes	WLL (metric) tonnes	Model	Rope Ø mm	Sheave dia. mm	Hooksize	øD1in	øD2in	B mmin	O mmin	TA mmin	TB mmin	TL mmin	Lin	T mmin	øZin	Weight lb
6097SRB35516550E	50	50	SRB 355 .16 .5 .50 .E	16	410 / 355	16	16.14	13.98	32.99	3.43	19.69	17.4	44.61	51.38	1.1	1.26	1,102.31
6097SRB36019563E	63	63	SRB 360 .19 .5 .63 .E	19	410 / 360	16	16.14	14.17	39.06	3.43	19.69	17.24	47.17	54.13	1.38	1.46	1,322.77
6097SRB36019580E	80	80	SRB 360 .19 .5 .80 .E	19	410 / 360	20	16.14	14.17	39.06	4.33	19.69	21.18	50.47	58.15	1.38	1.46	1,807.79
6097SRB40019580E	80	80	SRB 400 .19 .5 .80 .E	19	460 / 400	20	18.11	15.75	40.71	4.33	22.44	21.34	53.7	61.57	1.57	1.46	1,840.86
6097SRB40022580E	80	80	SRB 400 .22 .5 .80 .E	22	460 / 400	20	18.11	15.75	40.71	4.33	22.44	21.34	53.7	61.57	1.57	1.69	1,840.86
6097SRB45022580E	80	80	SRB 450 .22 .5 .80 .E	22	515 / 450	20	20.28	17.72	42.24	4.33	23.62	21.85	56.34	64.25	1.57	1.69	2,259.74
6097SRB450245100E	100	100	SRB 450 .24 .5 .100 .E	24	515 / 450	25	20.28	17.72	44.41	5.2	23.62	21.85	58.5	55.75	1.77	2.05	2,469.18
6097SRB450265100E	100	100	SRB 450 .26 .5 .100 .E	26	515 / 450	25	20.28	17.72	44.41	5.2	23.62	21.85	58.5	67.56	1.77	2.05	2,469.18
6097SRB528245125E	125	125	SRB 528 .24 .5 .125 .E	24	595 / 528	32	23.43	20.79	49.72	5.39	27.95	25.28	66.77	76.61	1.77	2.05	4,012.42
6097SRB528265125E	125	125	SRB 528 .26 .5 .125 .E	26	595 / 528	32	23.43	20.79	49.72	5.39	27.95	25.28	66.77	76.61	1.77	2.05	4,012.42
6097SRB528285125E	125	125	SRB 528 .28 .5 .125 .E	26	595 / 528	32	23.43	20.79	49.72	5.39	27.95	25.28	66.77	77.01	1.97	2.32	4,078.56
6097SRB528285160E	160	160	SRB 528 .28 .5 .160 .E	28	595 / 528	40	23.43	20.79	55.35	6.57	27.95	22.13	70.71	81.81	1.97	2.32	4,012.42
6097SRB670285200E	200	200	SRB 670 .28 .5 .200 .E	28	760 / 670	50	29.92	26.38	64.61	7.4	34.25	31.57	83.9	95.94	1.97	2.32	7,848.46
6097SRB670325200E	200	200	SRB 670 .32 .5 .200 .E	32	760 / 670	50	29.92	26.38	64.61	7.4	34.25	31.57	83.9	96.14	2.36	2.6	7,848.46

Blueprint

