

Fast Connector Socket FCS Spin Resistant - with bolt

Product information



Forged clevis fittings with bolt, nut and cutterpin for fast connection of steel wire rope. Connector shall be used with non-rotation resistant wire rope and may be used with rotation resistant wire rope.

The connector has to be moulded / casted on the steel wire rope with wirelock resin.

... [Read more](#)

Features: Designed for use with mobile cranes.


Material: Quenched and tempered cast steel.

Finish: Blue painted (P) or hot dip galvanized (G).

Warning: Compare the spelter's and the wire rope's minimum breaking load.

Fast Connector Socket FCS Spin Resistant - with bolt

Blueprint



Technical data

Part code	Code	Rope Ø range mm	MBL tonnes	Finish	A in	B in	C in	Ø H mm in	Ø P mm in	T in	W mm in	D, in	Ø D mm in	Ø J mm in	K in	TB mm in	TL mm in	Weight lb
122102600282	FCS 705 B.SR.G	23-26	75	Galvanized	4.53	4.84	2.36	1.1	2.01	0.87	2.01	4.09	2.36	3.74	3.54	5.43	11.73	24.25
122102600285	FCS 705 B.SR	23-26	75	Painted	4.53	4.84	2.36	1.1	2.01	0.87	2.01	4.09	2.36	3.74	3.54	5.43	11.73	24.25
122102900282	FCS 706 B.SR.G	27-29	90	Galvanized	5.51	5.98	2.56	1.26	2.24	0.98	2.24	4.49	2.76	4.21	4.57	6.3	14.06	35.27
122102900285	FCS 706 B.SR	27-29	90	Painted	5.51	5.98	2.56	1.26	2.24	0.98	2.24	4.49	2.76	4.21	4.57	6.3	14.06	35.27
122103200282	FCS 707 B.SR.G	30-32	125	Galvanized	5.91	6.26	2.87	1.42	2.48	1.1	2.48	4.96	3.15	4.69	4.72	6.5	15.04	39.68
122103200285	FCS 707 B.SR	30-32	125	Painted	5.91	6.26	2.87	1.42	2.48	1.1	2.48	4.96	3.15	4.69	4.72	6.5	15.04	39.68
122103600282	FCS 708 B.SR.G	33-36	125	Galvanized	6.3	6.73	2.87	1.54	2.72	1.1	2.72	4.96	3.35	4.92	5.12	7.28	15.91	50.71
122103600285	FCS 708 B.SR	33-36	125	Painted	6.3	6.73	2.87	1.54	2.72	1.1	2.72	4.96	3.35	4.92	5.12	7.28	15.91	50.71
122103900282	FCS 709 B.SR.G	37-39	150	Galvanized	6.93	7.36	3.15	1.65	2.99	1.18	2.99	5.59	3.54	5.35	5.59	7.91	17.44	63.93
122103900285	FCS 709 B.SR	37-39	150	Painted	6.93	7.36	3.15	1.65	2.99	1.18	2.99	5.59	3.54	5.35	5.59	7.91	17.44	63.93
122104200282	FCS 710 B.SR.G	40-42	170	Galvanized	7.4	7.8	3.46	1.77	2.99	1.3	2.99	6.14	3.74	5.59	5.91	8.23	18.66	79.37
122104200285	FCS 710 B.SR	40-42	170	Painted	7.4	7.8	3.46	1.77	2.99	1.3	2.99	6.14	3.74	5.59	5.91	8.23	18.66	79.37
122104800282	FCS 711 B.SR.G	43-48	225	Galvanized	8.27	9.13	3.94	2.05	3.5	1.54	3.5	6.93	4.33	6.57	6.89	9.33	21.34	127.87
122104800285	FCS 711 B.SR	43-48	225	Painted	8.27	9.13	3.94	2.05	3.5	1.54	3.5	6.93	4.33	6.57	6.89	9.33	21.34	127.87

Fast Connector Socket FCS Spin Resistant - with bolt
