

Fast Connector Socket FCS Spin Resistant - with pin

Product information



Forged clevis fittings with pin and cutterpin for fast connection of steel wire rope. Connector shall be used with non-rotation resistant wire rope and may be used with rotation resistant wire rope.

The connector has to be moulded / casted on the steel wire rope with [wirelock resin](#) ... [Read more](#)

Features: Designed for use with mobile cranes.


Material: Quenched and tempered cast steel.

Finish: Blue painted (P) or hot dip galvanized (G).

Warning: Compare the spelter's and the wire rope's minimum breaking load.

Fast Connector Socket FCS Spin Resistant - with pin

Blueprint



Technical data

Part code	Code	Rope Ø range mm	MBL tonnes	Finish	A in	B in	C in	Ø H mm in	Ø P mm in	T in	W mm in	D, in	Ø D mm in	Ø J mm in	K in	TB mm in	TL mm in	Weight lb
122102600292	FCS 705 P.SR	23-26	75	Galvanized	4.53	4.84	2.36	1.1	2.01	0.87	2.01	4.09	2.36	3.74	3.54	5.04	11.73	24.25
122102600295	FCS 705 P.SR	23-26	75	Painted	4.53	4.84	2.36	1.1	2.01	0.87	2.01	4.09	2.36	3.74	3.54	5.04	11.73	24.25
122102900292	FCS 706 P.SR	27-29	90	Galvanized	5.51	5.98	2.56	1.26	2.8	0.98	2.24	4.49	2.76	4.21	4.57	5.59	14.06	35.27
122102900295	FCS 706 P.SR	27-29	90	Painted	5.51	5.98	2.56	1.26	2.8	0.98	2.24	4.49	2.76	4.21	4.57	5.59	14.06	35.27
122103200295	FCS 707 P.SR	30-32	125	Painted	5.91	6.26	2.87	1.42	2.48	1.1	2.48	4.96	3.15	4.69	4.72	6.1	15.04	39.68
122103200292	FCS 707 P.SR	30-32	125	Galvanized	5.91	6.26	2.87	1.42	2.48	1.1	2.48	4.96	3.15	4.69	4.72	6.1	15.04	39.68
122103600295	FCS 708 P.SR	33-36	125	Painted	6.3	6.73	2.87	1.54	2.52	1.1	2.72	4.96	3.35	4.92	5.12	6.3	15.91	50.71
122103600292	FCS 708 P.SR	33-36	125	Galvanized	6.3	6.73	2.87	1.54	2.52	1.1	2.72	4.96	3.35	4.92	5.12	6.3	15.91	50.71
122103900292	FCS 709 P.SR	37-39	150	Galvanized	6.93	7.36	3.15	1.65	2.76	1.18	2.99	5.59	3.54	5.35	5.59	6.97	17.44	63.93
122103900295	FCS 709 P.SR	37-39	150	Painted	6.93	7.36	3.15	1.65	2.76	1.18	2.99	5.59	3.54	5.35	5.59	6.97	17.44	63.93
122104200295	FCS 710 P.SR	40-42	170	Painted	7.4	7.8	3.46	1.77	2.99	1.3	2.99	6.14	3.74	5.59	5.91	7.36	18.66	79.37
122104200292	FCS 710 P.SR	40-42	170	Galvanized	7.4	7.8	3.46	1.77	2.99	1.3	2.99	6.14	3.74	5.59	5.91	7.36	18.66	79.37
122104800295	FCS 711 P.SR	43-48	225	Painted	8.27	9.13	3.94	2.05	3.5	1.54	3.5	6.93	4.33	6.57	6.89	8.46	21.34	127.87
122104800292	FCS 711 P.SR	43-48	225	Galvanized	8.27	9.13	3.94	2.05	3.5	1.54	3.5	6.93	4.33	6.57	6.89	8.46	21.34	127.87

Fast Connector Socket FCS Spin Resistant - with pin
