

## Super Reeve Connector Socket SCS - with bolt

---

### Product information



A revolutionary evolution of the Fast Connector Socket. This socket line has the smallest connector diameter available in the market today, and still meets the respective EN standards. It has been designed to go through the smallest spaces in a crane reeving system.

This unique patent pending design allows refitting by pouring in the field, saving valuable down time compared to swaging techniques.


The standard finish of our sockets is blue. Hot dipped galvanized is also available [... Read more](#)

---

**Material:** Quenched and tempered cast steel.

## Super Reeve Connector Socket SCS - with bolt

### Blueprint



### Technical data

Part code	Code	Rope Ø range mm	MBL tonnes	Finish	A in	B in	C in	Ø Hmm in	Ø Pmm in	T in	Wmm in	D in	Ø D mm in	ØJ mm in	L in	TLmm in	TBmm in	Weight lb
122101600192	SCS 902 B.GAL	13-16	25	Galvanized	3.35	5.24	1.26	0.75	1.18	0.55	1.26	2.28	1.26	2.2	3.86	9.84	3.78	6.83
122101600195	SCS 902 B	13-16	25	Painted	3.35	5.24	1.26	0.75	1.18	0.55	1.26	2.28	1.26	2.2	3.86	9.84	3.78	6.83
122101900192	SCS 903 B.GAL	16-19	40	Galvanized	3.54	6.3	1.57	0.87	1.38	0.63	1.5	2.76	1.57	2.56	4.49	11.42	4.21	10.58
122101900195	SCS 903 B	16-19	40	Painted	3.54	6.3	1.57	0.87	1.38	0.63	1.5	2.76	1.57	2.56	4.49	11.42	4.21	10.58
122102200192	SCS 904 B.GAL	20-22	55	Galvanized	4.21	7.24	1.77	1.02	1.61	0.75	1.73	3.15	1.73	3.03	5.12	13.23	4.84	17.64
122102200195	SCS 904 B	20-22	55	Painted	4.21	7.24	1.77	1.02	1.61	0.75	1.73	3.15	1.73	3.03	5.12	13.23	4.84	17.64
122102600192	SCS 905 B.GAL	23-26	75	Galvanized	4.53	8.31	2.36	1.22	1.97	0.87	2.01	4.09	2.05	3.46	5.59	15.2	5.55	26.46
122102600195	SCS 905 B	23-26	75	Painted	4.53	8.31	2.36	1.22	1.97	0.87	2.01	4.09	2.05	3.46	5.59	15.2	5.55	26.46
122102900192	SCS 906 B.GAL	27-29	90	Galvanized	5.51	8.46	2.56	1.34	2.24	0.98	2.24	4.49	2.28	3.78	6.26	16.54	6.3	35.27
122102900195	SCS 906 B	27-29	90	Painted	5.51	8.46	2.56	1.34	2.24	0.98	2.24	4.49	2.28	3.78	6.26	16.54	6.3	35.27
122103200192	SCS 907 B.GAL	30-32	125	Galvanized	5.91	10.24	2.87	1.42	2.48	1.1	2.48	4.96	2.52	4.33	6.97	19.02	6.5	50.71
122103200195	SCS 907 B	30-32	125	Painted	5.91	10.24	2.87	1.42	2.48	1.1	2.48	4.96	2.52	4.33	6.97	19.02	6.5	50.71
122103600192	SCS 908 B.GAL	33-36	125	Galvanized	6.69	10.24	2.87	1.57	2.52	1.1	2.72	4.96	2.68	4.49	7.76	19.8	7.28	55.12
122103600195	SCS 908 B	33-36	125	Painted	6.69	10.24	2.87	1.57	2.52	1.1	2.72	4.96	2.68	4.49	7.76	19.8	7.28	55.12