

Super Reeve Connector Socket SCS Spin resistant - with bolt

Product information



A revolutionary evolution of the Fast Connector Socket. This socket line has the smallest connector diameter available in the market today, and still meets the respective EN standards. It has been designed to go through the smallest spaces in a crane reeving system.

This unique patent pending design allows refitting by pouring in the field, saving valuable down time compared to swaging techniques.

The standard finish of our sockets is blue. Hot dipped galvanized is also available.

... [Read more](#)

Material: Quenched and tempered cast steel.

Super Reeve Connector Socket SCS Spin resistant - with bolt

Technical data

| Part code | Code | Rope Ø range mm | MBL tonnes | Finish | A in | B in | C in | Ø Hmm in | Ø Pmm in | T in | Wmm in | D, in | Ø D mm in | ØJ mm in | L in | TLmm in | TBmm in | Weight lb |
|--------------|------------------|-----------------|------------|------------|------|-------|------|----------|----------|------|--------|-------|-----------|----------|-------|---------|---------|-----------|
| 122101600302 | SCS 903 B.SR.GAL | 13-16 | 25 | Galvanized | 3.35 | 5.24 | 1.26 | 0.75 | 1.18 | 0.55 | 1.26 | 2.28 | 1.26 | 2.2 | 3.86 | 9.84 | 3.78 | 6.83 |
| 122101600305 | SCS 902 B.SR | 13-16 | 25 | Painted | 3.35 | 5.24 | 1.26 | 0.75 | 1.18 | 0.55 | 1.26 | 2.28 | 1.26 | 2.2 | 3.86 | 9.84 | 3.78 | 6.83 |
| 122101900302 | SCS 902 B.SR.GAL | 16-19 | 40 | Galvanized | 3.54 | 6.3 | 1.57 | 0.87 | 1.38 | 0.63 | 1.5 | 2.76 | 1.57 | 2.56 | 4.49 | 11.42 | 4.21 | 10.58 |
| 122101900305 | SCS 903 B.SR | 16-19 | 40 | Painted | 3.54 | 6.3 | 1.57 | 0.87 | 1.38 | 0.63 | 1.5 | 2.76 | 1.57 | 2.56 | 4.49 | 11.42 | 4.21 | 10.58 |
| 122102200302 | SCS 904 B.SR.GAL | 20-22 | 55 | Galvanized | 4.21 | 7.24 | 1.77 | 1.02 | 1.61 | 0.75 | 1.73 | 3.15 | 1.73 | 3.03 | 5.12 | 13.23 | 4.84 | 17.64 |
| 122102200305 | SCS 904 B.SR | 20-22 | 55 | Painted | 4.21 | 7.24 | 1.77 | 1.02 | 1.61 | 0.75 | 1.73 | 3.15 | 1.73 | 3.03 | 5.12 | 13.23 | 4.84 | 17.64 |
| 122102600302 | SCS 905 B.SR.GAL | 23-26 | 75 | Galvanized | 4.53 | 8.31 | 2.36 | 1.22 | 1.97 | 0.87 | 2.01 | 4.09 | 2.05 | 3.46 | 5.59 | 15.2 | 5.55 | 26.46 |
| 122102600305 | SCS 905 B.SR | 23-26 | 75 | Painted | 4.53 | 8.31 | 2.36 | 1.22 | 1.97 | 0.87 | 2.01 | 4.09 | 2.05 | 3.46 | 5.59 | 15.2 | 5.55 | 26.46 |
| 122102900302 | SCS 906 B.SR.GAL | 27-29 | 90 | Galvanized | 5.51 | 8.46 | 2.56 | 1.34 | 2.24 | 0.98 | 2.24 | 4.49 | 2.28 | 3.78 | 6.26 | 16.54 | 6.3 | 35.27 |
| 122102900305 | SCS 906 B.SR | 27-29 | 90 | Painted | 5.51 | 8.46 | 2.56 | 1.34 | 2.24 | 0.98 | 2.24 | 4.49 | 2.28 | 3.78 | 6.26 | 16.54 | 6.3 | 35.27 |
| 122103200302 | SCS 907 B.SR.GAL | 30-32 | 125 | Galvanized | 5.91 | 10.24 | 2.87 | 1.42 | 2.48 | 1.1 | 2.48 | 4.96 | 2.52 | 4.33 | 6.97 | 19.02 | 6.5 | 50.71 |
| 122103200305 | SCS 907 B.SR | 30-32 | 125 | Painted | 5.91 | 10.24 | 2.87 | 1.42 | 2.48 | 1.1 | 2.48 | 4.96 | 2.52 | 4.33 | 6.97 | 19.02 | 6.5 | 50.71 |
| 122103600302 | SCS 908 B.SR.GAL | 33-36 | 125 | Galvanized | 6.69 | 10.24 | 2.87 | 1.57 | 2.52 | 1.1 | 2.72 | 4.96 | 2.68 | 4.49 | 7.76 | 19.8 | 7.28 | 55.12 |
| 122103600305 | SCS 908 B.SR | 33-36 | 125 | Painted | 6.69 | 10.24 | 2.87 | 1.57 | 2.52 | 1.1 | 2.72 | 4.96 | 2.68 | 4.49 | 7.76 | 19.8 | 7.28 | 55.12 |
| 122104200305 | SCS 910 B.SR | 40-42 | 170 | Painted | 6.3 | 11.14 | 3.46 | 1.77 | 2.99 | 1.3 | 2.99 | 6.14 | 3.31 | 5.47 | 7.68 | 20.91 | 8.23 | 92.59 |
| 122104200302 | SCS 910 B.SR.GAL | 40-42 | 170 | Galvanized | 6.3 | 11.14 | 3.46 | 1.77 | 2.99 | 1.3 | 2.99 | 6.14 | 3.31 | 5.47 | 7.68 | 20.91 | 8.23 | 92.59 |
| 122105400305 | SCS 912 B.SR | 49-54 | 280 | Painted | 8.86 | 14.69 | 4.25 | 2.36 | 3.74 | 1.77 | 3.98 | 7.64 | 4.13 | 7.28 | 11.02 | 27.8 | 10.35 | 205.03 |
| 122105400302 | SCS 912 B.SR.GAL | 49-54 | 280 | Galvanized | 8.86 | 14.69 | 4.25 | 2.36 | 3.74 | 1.77 | 3.98 | 7.64 | 4.13 | 7.28 | 11.02 | 27.8 | 10.35 | 205.03 |