Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

# Super reeve Connector Sockets SCS - with pin

**Product information**

**General:**
A revolutianary evolution of the Fast Connector Socket. This socket line has the smallest connector diameter available inthe market today, and still meets the respective EN standards. It has been designed to go through the smallest spaces in a crane reeving system.
This unique patent pending design allows refitting by pouring in the field, saving valuable down time compared to swaging techniques.
The standard finish of our sockets is blue. Hot dipped galvanized is also available.

**Option:** hot dip galvanized.

... *Read more*

**Material:** Quenched and tempered cast steel.

**Industrial Rigging & Supply**
info@industrialrigging.ca
+1 (519) 624-9697

© October 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

# Super reeve Connector Sockets SCS - with pin

## Blueprint



## Technical data

| Part code | Code | Rope Ø range mm | MBL tonnes | Finish | A in | B in | C in | øH in | øP mm in | T in | W in | D in | øD in | øJ in | L in | TB in | TLmm in | Weight lb |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 122101600235 | SCS 902 P | 13-16 | 25 | Painted | 3.35 | 5.24 | 1.26 | 0.75 | 1.18 | 0.55 | 1.26 | 2.28 | 1.26 | 2.2 | 3.86 | 3.35 | 9.84 | 6.83 |
| 122101600232 | SCS 902 P | 13-16 | 25 | Galvanized | 3.35 | 5.24 | 1.26 | 0.75 | 1.18 | 0.55 | 1.26 | 2.28 | 1.26 | 2.2 | 3.86 | 3.35 | 9.84 | 6.83 |
| 122101900235 | SCS 903 P | 16-19 | 40 | Painted | 3.54 | 6.3 | 1.57 | 0.87 | 1.38 | 0.63 | 1.5 | 2.76 | 1.57 | 2.56 | 4.49 | 3.74 | 11.42 | 10.58 |
| 122101900232 | SCS 903 P | 16-19 | 40 | Galvanized | 3.54 | 6.3 | 1.57 | 0.87 | 1.38 | 0.63 | 1.5 | 2.76 | 1.57 | 2.56 | 4.49 | 3.74 | 11.42 | 10.58 |
| 122102200235 | SCS 904 P | 20-22 | 55 | Painted | 4.21 | 7.24 | 1.77 | 1.02 | 1.61 | 0.75 | 1.73 | 3.15 | 1.73 | 3.03 | 5.12 | 4.33 | 13.23 | 17.64 |
| 122102200232 | SCS 904 P | 20-22 | 55 | Galvanized | 4.21 | 7.24 | 1.77 | 1.02 | 1.61 | 0.75 | 1.73 | 3.15 | 1.73 | 3.03 | 5.12 | 4.33 | 13.23 | 17.64 |
| 122102600235 | SCS 905 P | 23-26 | 75 | Painted | 4.53 | 8.31 | 2.36 | 1.22 | 1.97 | 0.87 | 2.01 | 4.09 | 2.05 | 3.46 | 5.59 | 5.04 | 15.2 | 26.46 |
| 122102600232 | SCS 905 P | 23-26 | 75 | Galvanized | 4.53 | 8.31 | 2.36 | 1.22 | 1.97 | 0.87 | 2.01 | 4.09 | 2.05 | 3.46 | 5.59 | 5.04 | 15.2 | 26.46 |
| 122102900235 | SCS 906 P | 27-29 | 90 | Painted | 5.51 | 8.46 | 2.56 | 1.34 | 2.24 | 0.98 | 2.24 | 4.49 | 2.28 | 3.78 | 6.26 | 5.59 | 16.54 | 35.27 |
| 122102900232 | SCS 906 P | 27-29 | 90 | Galvanized | 5.51 | 8.46 | 2.56 | 1.34 | 2.24 | 0.98 | 2.24 | 4.49 | 2.28 | 3.78 | 6.26 | 5.59 | 16.54 | 35.27 |
| 122103200235 | SCS 907 P | 30-32 | 125 | Painted | 5.91 | 10.24 | 2.87 | 1.42 | 2.48 | 1.1 | 2.48 | 4.96 | 2.52 | 4.33 | 6.97 | 6.1 | 19.02 | 50.71 |
| 122103200232 | SCS 907 P | 30-32 | 125 | Galvanized | 5.91 | 10.24 | 2.87 | 1.42 | 2.48 | 1.1 | 2.48 | 4.96 | 2.52 | 4.33 | 6.97 | 6.1 | 19.02 | 50.71 |
| 122103600235 | SCS 908 P | 33-36 | 125 | Painted | 6.69 | 10.24 | 2.87 | 1.57 | 2.52 | 1.1 | 2.72 | 4.96 | 2.68 | 4.49 | 7.76 | 5.12 | 19.8 | 55.12 |
| 122103600232 | SCS 908 P | 33-36 | 125 | Galvanized | 6.69 | 10.24 | 2.87 | 1.57 | 2.52 | 1.1 | 2.72 | 4.96 | 2.68 | 4.49 | 7.76 | 5.12 | 19.8 | 55.12 |


© October 2026 - All Rights Reserved