

Super reeve Connector Sockets SCS - with pin

Product information



General:

A revolutionary evolution of the Fast Connector Socket. This socket line has the smallest connector diameter available in the market today, and still meets the respective EN standards. It has been designed to go through the smallest spaces in a crane reeving system.

This unique patent pending design allows refitting by pouring in the field, saving valuable down time compared to swaging techniques.

The standard finish of our sockets is blue. Hot dipped galvanized is also available.


Option: hot dip galvanized.

[... Read more](#)

Material: Quenched and tempered cast steel.

Super reeve Connector Sockets SCS - with pin

Blueprint



Technical data

Part code	Code	Rope Ø range mm	MBL tonnes	Finish	A in	B in	C in	øH in	øP mm	T in	Wmm in	D in	øD in	øJ in	L in	TBmm in	TLmm in	Weight lb
122101600235	SCS 902 P	13-16	25	Painted	3.35	5.24	1.26	0.75	1.18	0.55	1.26	2.28	1.26	2.2	3.86	3.35	9.84	6.83
122101600232	SCS 902 P	13-16	25	Galvanized	3.35	5.24	1.26	0.75	1.18	0.55	1.26	2.28	1.26	2.2	3.86	3.35	9.84	6.83
122101900235	SCS 903 P	16-19	40	Painted	3.54	6.3	1.57	0.87	1.38	0.63	1.5	2.76	1.57	2.56	4.49	3.74	11.42	10.58
122101900232	SCS 903 P	16-19	40	Galvanized	3.54	6.3	1.57	0.87	1.38	0.63	1.5	2.76	1.57	2.56	4.49	3.74	11.42	10.58
122102200235	SCS 904 P	20-22	55	Painted	4.21	7.24	1.77	1.02	1.61	0.75	1.73	3.15	1.73	3.03	5.12	4.33	13.23	17.64
122102200232	SCS 904 P	20-22	55	Galvanized	4.21	7.24	1.77	1.02	1.61	0.75	1.73	3.15	1.73	3.03	5.12	4.33	13.23	17.64
122102600235	SCS 905 P	23-26	75	Painted	4.53	8.31	2.36	1.22	1.97	0.87	2.01	4.09	2.05	3.46	5.59	5.04	15.2	26.46
122102600232	SCS 905 P	23-26	75	Galvanized	4.53	8.31	2.36	1.22	1.97	0.87	2.01	4.09	2.05	3.46	5.59	5.04	15.2	26.46
122102900235	SCS 906 P	27-29	90	Painted	5.51	8.46	2.56	1.34	2.24	0.98	2.24	4.49	2.28	3.78	6.26	5.59	16.54	35.27
122102900232	SCS 906 P	27-29	90	Galvanized	5.51	8.46	2.56	1.34	2.24	0.98	2.24	4.49	2.28	3.78	6.26	5.59	16.54	35.27
122103200235	SCS 907 P	30-32	125	Painted	5.91	10.24	2.87	1.42	2.48	1.1	2.48	4.96	2.52	4.33	6.97	6.1	19.02	50.71
122103200232	SCS 907 P	30-32	125	Galvanized	5.91	10.24	2.87	1.42	2.48	1.1	2.48	4.96	2.52	4.33	6.97	6.1	19.02	50.71
122103600235	SCS 908 P	33-36	125	Painted	6.69	10.24	2.87	1.57	2.52	1.1	2.72	4.96	2.68	4.49	7.76	5.12	19.8	55.12
122103600232	SCS 908 P	33-36	125	Galvanized	6.69	10.24	2.87	1.57	2.52	1.1	2.72	4.96	2.68	4.49	7.76	5.12	19.8	55.12