

Overhaul Ball with Swivel Eye-Hook

Product information



The weight of the overhaul balls in this segment are based on average boom lengths and efficiency loss in mobile and crawler cranes. The low friction and easy to access hook swivel design makes the OHB series an excellent choice for a wide variety of crane applications.

- Bottom and top swiveling hook
- High quality, low friction thrust bearing
- Becket size optimized for Ropeblock Sockets such as Open Wedge (OWS), Open Spelter Sockets (OSS), Fast Connector Sockets (FCS) or Super Reeve Connector Sockets (SCS)
- Forged high tensile steel DIN hooks
- Body made of forged bar material
- High impact resistant body

... [Read more](#)


Temperature range: -40 up to +80°C

Finish: C3M finish, signal yellow

Safety factor: 4:1

Overhaul Ball with Swivel Eye-Hook

Blueprint



Technical data

Part code	WLL	Rope Ø mm	B in	Omm in	TA mm in	TL mm in	T in	øZ mm in	Weight lb
6097OHB3260C1	7,000	11-13	7.87	1.61	8.66	19.69	0.87	1.06	132.28
6097OHB3260C2	7,000	14-16	7.87	1.61	8.66	19.88	1.1	1.26	132.28
6097OHB580C2	11,000	14-16	8.66	1.93	9.37	22.28	1.1	1.26	176.37
6097OHB6380C2	13,800	14-16	8.66	1.93	9.37	22.28	1.1	1.26	176.37
6097OHB8130C3	17,600	18-19	12.2	1.93	10.12	28.31	1.38	1.46	286.6
6097OHB8170C3	17,600	18-19	13.39	1.93	10.94	26.81	1.38	1.46	374.79
6097OHB8250C3	17,600	18-19	15.75	1.93	12.52	34.02	1.38	1.46	551.16
6097OHB10210C4	22,000	20-22	14.96	1.93	11.73	29.57	1.57	1.69	462.97
6097OHB10250C5	22,000	24-26	15.75	1.93	12.52	30.35	1.77	2.05	551.16
6097OHB125250C5	27,500	24-26	15.75	2.17	12.52	32.64	1.77	2.05	551.16
6097OHB125350C5	27,500	24-26	17.72	2.17	13.78	34.61	1.77	2.05	771.62
6097OHB16350C5	35,200	24-26	17.72	2.32	12.52	38.66	1.77	2.05	771.62
6097OHB16450C5	35,200	24-26	17.32	2.32	15.75	38.27	1.77	2.05	992.08
6097OHB20550C6	44,000	27-29	18.5	2.72	16.02	42.28	1.97	2.32	1,212.54
6097OHB20550C7	44,000	30-32	18.5	2.72	16.02	42.68	2.36	2.56	1,212.54
6097OHB25680C7	55,000	30-32	20.08	2.72	18.11	42.44	2.36	2.56	1,499.14
6097OHB25680C8	55,000	34-36	20.08	2.72	18.11	42.44	2.36	2.56	1,499.14
6097OHB25800C8	55,000	34-36	24.02	2.72	18.11	46.38	2.36	2.56	1,763.7
6097OHB25800C7	55,000	30-32	24.02	2.72	18.11	46.38	2.36	2.56	1,763.7