

Round Overhaul Balls

Product information



The weight of the overhaul balls in this segment are based on average boom lengths and efficiency loss in mobile and crawler cranes. The low friction and easy to access hook swivel design makes the OHB series an excellent choice for a wide variety of crane applications.

- Top swiveling stud-eye
- High quality, low friction thrust bearing
- Becket size optimized for Ropeblock Sockets such as Open Wedge (OWS), Open Spelter Sockets (OSS), Fast Connector Sockets (FCS) or Super Reeve Connector Sockets (SCS)
- Forged alloy steel eye hooks
- Body made of forged bar material
- Impact resistant ductile body

... [Read more](#)


Temperature range: -40 up to +80°C

Finish: C3M finish, signal yellow

Safety factor: 4:1

Round Overhaul Balls

Blueprint



Technical data

Part code	WLL	B in	Omm in	øTA mm in	TL mm in	T in	øZ mm in	Weight lb
6097OHBB45451	10,000	7.8	1.38	9.06	23.23	0.87	1.06	99.21
6097OHBB45501	10,000	7.8	1.69	9.06	26.22	0.87	1.06	110.23
6097OHBB451002	10,000	11.38	1.38	12.28	25.59	1.1	1.3	220.46
6097OHBB451102	10,000	11.38	1.69	12.28	27.44	1.1	1.3	242.51
6097OHBB451402	10,000	12.56	1.38	13.54	26.77	1.1	1.3	308.65
6097OHBB451452	10,000	12.56	1.69	13.54	28.94	1.1	1.3	319.67
6097OHBB7501	16,000	7.8	1.69	9.06	26.22	0.87	1.06	110.23
6097OHBB7802	16,000	10	1.69	11.02	26.22	1.1	1.3	176.37
6097OHBB71102	16,000	11.38	1.69	12.28	27.44	1.1	1.3	242.51
6097OHBB71453	16,000	12.56	1.69	13.54	28.94	1.38	1.46	319.67
6097OHBB111803	24,000	13.11	2.09	14.57	33.03	1.38	1.46	396.83
6097OHBB112654	24,000	15.39	2.09	16.73	35.87	1.57	1.69	584.23
6097OHBB113204	24,000	16.42	2.09	17.72	36.89	1.57	1.69	705.48
6097OHBB115304	24,000	20	2.09	21.06	40.43	1.57	1.69	1,168.45
6097OHBB181955	40,000	13.11	3.07	14.57	38.31	1.77	2.05	429.9
6097OHBB183306	40,000	16.42	3.07	17.72	42.01	1.97	2.32	727.53
6097OHBB185456	40,000	20	3.07	21.06	45.55	1.97	2.32	1,201.52