Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Vertical Lifting Clamp TS-R

Product information



Clamp for vertical lifting and transporting of stainless steel plates and structures. Pivot and cam are made of stainless steel. Body and lock lever are nickel plated to prevent corrosion due to carbon contamination.

Features:

- Pivot and cam are made of stainless steel
- Body and lock lever are nickel plated to prevent corrosion due to carbon contamination
- TSU-R / TSEU-R come with articulated lifting shackle for universal lifting flexibility at various angles
- TS-R / TSE-R come with standard lifting shackle
- Always equipped with a safety mechanism, ensuring the clamp does not slip when lifting force is applied and when the load is being lowered
- Clamp is locked in closed as well as open position
- Lightweight design for easy handling
- Tough quality heavy-duty welded shell body
- Maintenance-friendly, easy to exchange parts which are available upon request

... *Read more*


Marking: According to standard, CE-mark, Type, serial number, WLL, Jaw opening.
Finish: Nickel plated.
Standard: EN 13155
Note: Hardness level of the material surface may not exceed HRC 37/345 Hb
Warning: Min. load is 10% of max. WLL.

© November 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Vertical Lifting Clamp TS-R

Blueprint



Technical data

Part code	Code	WLL (metric) tonnes	Jaw width in	S in	T in	U in	V in	W in	X in	Y in	Weight lb
502100080130634	0.75 TS-R	0.75	0-0.51	1.85	1.18	7.95	3.94	1.46	1.46	0.39	3.75
502100080130630	0.75 TSU-R	0.75	0-0.51	1.85	1.18	7.99	3.94	1.46	1.46	0.39	3.97
502100100250634	1 TSE-R	1	0-0.98	2.2	1.77	10.35	5.55	1.46	1.85	0.59	7.72
502100100250630	1 TSEU-R	1	0-0.98	2.2	1.97	11.5	5.55	1.46	1.85	0.59	8.38
502100200350634	2 TSE-R	2	0-1.38	3.07	2.52	13.23	7.2	2.2	2.2	0.63	15.43
502100200350630	2 TSEU-R	2	0-1.38	3.07	2.76	14.65	7.2	2.2	2.2	0.63	17.64
502100300350634	3 TSE-R	3	0-1.38	3.07	2.52	13.23	7.2	2.2	2.2	0.63	15.43
502100300350630	3 TSEU-R	3	0-1.38	3.07	2.76	14.65	7.2	2.2	2.2	0.63	17.64
502100450450634	4.5 TSE-R	4.5	0-1.77	3.35	2.76	16.73	8.98	2.36	3.07	0.79	35.27
502100450450630	4,5 TSEU-R	4.5	0-1.77	3.35	2.76	16.97	8.98	2.36	3.07	0.79	36.38
502100600500634	6 TSE-R	6	0-1.97	4.49	2.95	19.29	10.2	3.23	3.07	0.79	46.3
502100600500630	6 TSEU-R	6	0-1.97	4.49	3.07	20.75	10.2	3.23	3.07	1.26	52.91
502100750550634	7.5 TSE-R	7.5	0-2.17	4.37	2.95	20.55	10.51	2.76	3.39	0.79	57.32
502100750550630	7,5 TSEU-R	7.5	0-2.17	4.49	3.07	22.05	10.51	2.76	3.39	1.26	61.73

© November 2026 - All Rights Reserved