Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Vertical Lifting Clamp TBLC - Non marking

Product information



Clamp for vertical lifting and transporting of all plates, blocks and structures with parallel sides without marking, scratching and or damaging the material surface. Perfect for lifting materials such as (stainless) steel, aluminum, nature stone, composite, painted materials, wood, glass, plastic, etc .The clamp is locked in the open position. To perform lifting, the operator must activate the handle and hold it up while the force on the lifting eye is going upwards. When laying down the load, the clamp automaticly locks itself open.

Features:

- 2 special synthetic anti-friction pads to guarantee non-marking.
- Lightweight design and easy to use.
- Tough quality heavy duty body.
- Maintenance-friendly, easy to exchange parts. Parts available upon request.
- No minimal WLL needed.

... *Read more*

Marking: According to standard, CE-mark
Temperature range: -10°C to +30°C.
Standard: EN 13155

© November 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Vertical Lifting Clamp TBLC - Non marking

Blueprint



Technical data

Part code	Code	WLL (metric) tonnes	Jaw width in	V min-max in	U min-max in	S in	T in	X in	Y in	Weight lb
502100051100820	0.5 TBLC	0.5	1.18-4.33	10.63-12.8	12.01-18.11	3.74	1.77	3.15	0.59	15.43
502100102300820	1 TBLC	1	3.94-9.06	16.73-20.87	14.96-25.79	4.72	1.77	3.15	0.59	27.12
502100203600820	2 TBLC	2	8.66-14.17	22.83-26.57	16.14-28.94	5.51	1.77	3.15	0.59	39.68
502100305000820	3 TBLC	3	13.78-19.69	28.54-32.87	20.87-35.43	7.01	2.52	3.94	0.63	72.75

© November 2026 - All Rights Reserved