

Horizontal Lifting Clamp Terrier FHX/FHSX

Product information



For horizontal lifting and transporting of steel plates and other non-deflecting materials. Jaw openings available from: 0 to 150 mm. Only to be used and only sold in pairs.

Model FHX: Standard clamp

Model FHSX: Clamp with enlarged jaw opening.

- Compact design and high lifting capacity
- Lightweight design for easy handling
- Tough quality heavy duty welded body

... [Read more](#)

Marking: According to standard, CE-marked, Type, serial number, WLL, Jaw opening.

Temperature range: - 40°C up to +100°C


Standard: EN 13155

Note: Must always be used in pairs (or multiple pairs)

Warning: Hardness level of the material surface may not exceed 37 Hrc (345 Hb, 1166 N/mm²)

Horizontal Lifting Clamp Terrier FHX/FHSX

Blueprint



Technical data

Part code	Code	WLL (metric) tonnes	Jaw width in	V in	S in	W in	T in	H in	X in	U in	Y in	Weight lb
502100100350670	1 FHX	1	0-1.38	5.51	3.9	0.39	0.98	0.45	2.56	7.4	0.59	5.73
502100200600670	2 FHX	2	0-2.36	7.09	4.65	0.59	1.2	0.77	3.54	11.3	0.63	15.43
502100201000670	2 FHSX	2	0-3.94	7.09	4.72	0.59	1.2	0.77	3.54	15.08	0.59	20.28
502100300600670	3 FHX	3	0-2.36	7.09	4.65	0.79	1.2	0.77	3.54	11.46	0.63	17.64
502100301000670	3 FHSX	3	0-3.94	7.09	4.72	0.79	1.2	0.77	3.54	15.24	0.59	22.05
502100400600670	4 FHX	4	0-2.36	8.66	5.71	0.98	1.2	0.77	4.13	11.97	0.79	28.66
502100401000670	4 FHSX	4	0-3.94	8.66	5.71	0.98	1.2	0.77	4.13	16.3	0.79	33.07
502100600600670	6 FHX	6	0-2.36	8.66	5.71	0.98	1.2	0.77	4.33	12.09	0.79	30.86
502100601000670	6 FHSX	6	0-3.94	8.66	5.71	0.98	1.2	0.77	4.72	16.3	0.79	36.38
502100800600670	8 FHX	8	0-2.36	8.86	5.31	1.38	1.2	0.77	4.72	13.23	1.18	41.89
502100801000670	8 FHSX	8	0-3.94	8.86	5.31	1.38	1.2	0.77	4.72	16.85	1.18	46.3
502101000600670	10 FHX	10	0-2.36	8.86	5.31	1.38	1.2	0.77	4.72	13.23	1.18	41.89
502101001000670	10 FHSX	10	0-3.94	8.86	5.31	1.38	1.2	0.77	4.72	16.85	1.18	48.5
502101200600670	12 FHX	12	0-2.36	8.86	5.31	1.38	1.2	0.77	4.72	13.23	1.18	41.89
502101201000670	12 FHSX	12	0-3.94	8.86	5.31	1.38	1.2	0.77	4.72	16.85	1.18	48.5
502101500600670	15 FHX	15	0-2.36	10.31	5.79	1.38	1.69	0.85	6.3	13.54	1.38	66.14
502101501500670	15 FHSX	15	0-5.91	13.78	9.45	1.38	1.77	1.08	5.51	26.18	1.38	116.85
502102500600670	25 FHX	25	0-2.36	10.31	5.79	1.57	1.69	0.85	6.89	13.74	1.38	72.75