Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Horizontal Lifting Clamp FHX-V

Product information



For horizontal lifting and transporting of steel plates and other non-deflecting materials. The FHX-V lifting clamp has a spring attached to the cam assembly. The spring makes sure that the clamp will/can be closed and fixed on any desired spot. One of the major advantages of this clamp is that only one person is able to place the clamps and to guide the hoist.
Jaw openings available from: 0 to 60 mm.

Features:

- Pre-tensioned spring cam feature for easy single operator usage
- Clamp can be closed and fixed on any desired spot
- Compact & lightweight design for easy handling
- Tough quality heavy duty welded body

... *Read more*

Marking: According to standard, CE-mark, Type, serial number, WLL, Jaw opening.
Temperature range: - 40°C up to +100°C
Standard: EN 13155
Note: Must always be used in pairs (or multiple pairs)
Warning: Hardness level of the material surface may not exceed 37 HrC (345 Hb, 1166 N/mm2)

© November 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Horizontal Lifting Clamp FHX-V

Blueprint



Technical data

Part code	Code	WLL (metric) tonnes	Jaw width in	V in	S in	W in	T in	H in	U in	X in	Y in	Weight lb
502100100350680	1 FHX-V	1	0-1.38	5.51	3.9	0.39	1.04	0.47	7.4	3.35	0.59	6.61
502100200600680	2 FHX-V	2	0-2.36	7.09	4.49	0.59	1.2	0.75	11.26	4.92	0.63	17.64
502100300600680	3 FHX-V	3	0-2.36	7.87	4.92	0.79	1.2	0.75	11.89	5.51	0.79	26.9
502100400600680	4 FHX-V	4	0-2.36	8.66	5.47	1.18	1.2	0.75	12.44	6.5	0.79	37.48
502100600600680	6 FHX-V	6	0-2.36	8.66	5.47	1.18	1.2	0.75	12.44	6.5	0.79	37.48

© November 2026 - All Rights Reserved