

## Horizontal Pipe Lifting Clamp TTL

### Product information



Clamp for horizontal lifting and transporting of tubes, pipes, tube bundles, rolls and other solid round materials. The clamp is locked in the open position. To perform lifting, the operator must activate the handle and hold it up while the force on the lifting eye is going upwards. When laying down the load, the clamp automatically locks itself open.

#### Features:

- Lightweight design and easy to use.
- Tough quality body.
- Can be delivered with protection to avoid damaging of the load.
- Higher WLL or jaw openings available upon request.

... [Read more](#)


**Marking:** According to standard, CE-marked, Type, serial number, WLL, Jaw opening

**Temperature range:** -40°C to + 100°C

**Standard:** EN 13155

## Horizontal Pipe Lifting Clamp TTL

### Blueprint



### Technical data

Part code	Code	WLL (metric tonnes)	Jaw width in	Rmm in	T in	U min-max in	V min-max in	X mm in	Ymm in	Weight lb
502100051140810	0.5 TTL	0.5	1.9-4.5	1.9-4.5	1.77	11.81-15.75	5.75-8.15	1.85	0.59	9.92
502100102190810	1 TTL	1	4.5-8.63	4.5-8.63	1.77	16.93-24.21	4.33-6.69	1.85	0.59	19.84
502100203680810	2 TTL	2	8.63-14.49	8.63-14.49	2.52	26.38-37.6	8.86-12.6	2.2	0.63	68.34
502100305080810	3 TTL	3	14.49-20	14.49-20	2.52	34.45-45.87	23.23-27.95	2.2	0.63	85.98