

Pulling and Lifting Hoist, TIRFOR® TU

Product information

Portable hoist to lift and pull loads, for utilisation in numerous configurations with long cable lengths.

- Low weight - quick installation
- No limitation in terms of cable length
- Manageable, light-weight, robust, powerful
- Increase load capacity with deflection sheaves
- Overload protection
- Precise load placement within millimetres

Marking: According to standard

Standard: EN 13157

Safety factor: 5:1



| Part code | Code | WLL (metric) tonnes | Lifting height m | Rope Ø mm | Dim. of the machine mm | Handle open/closed mm | Weight kg |
|-----------------|-------|------------------------|---------------------|--------------|---------------------------|--------------------------|--------------|
| 501100080000110 | TU-8 | 0.8 | - | - | 527 x 265 x 108 | 620 - 395 | 8.4 |
| 501100082000110 | TU-8 | 0.8 | 20 | 8,3 | 527 x 265 x 108 | 620 - 395 | 15.5 |
| 501100160000110 | TU-16 | 1.6 | - | - | 660 x 330 x 140 | 1190 - 680 | 18 |
| 501100162000110 | TU-16 | 1.6 | 20 | 11,5 | 660 x 330 x 140 | 1190 - 680 | 33.5 |
| 501100320000110 | TU-32 | 3.2 | - | - | 676 x 330 x 156 | 1190 - 680 | 27 |
| 501100322000110 | TU-32 | 3.2 | 20 | 16,3 | 676 x 330 x 156 | 1190 - 680 | 56 |