



Pulling Hoist, MINIFOR™

Product information

MINIFOR™ hoists are used with a Maxiflex wire rope. They can be used to lift or pull objects over great distances depending on the wire rope length. They are suitable for use in numerous configurations. They are operated through a pushbutton control. Optionally, the MINIFOR™ hoist can be equipped with a wire rope reeling device or a wireless remote control.

TR110 is fitted with an overload protection system

- Capacity 100 kg, 300 kg or 500 kg
- Quick installation
- Easy to use, light-weight, robust, powerful
- Available as single phase and three phase model
- Excellent capacity / weight ratio
- Unlimited wire rope travel
- Pendant control (up/down/emergency stop) 2,5 m
- Aluminium alloy design
- Swivelling suspension hook
- Protection: IP55 (Control: IP65)
- Upper and lower limit switches

Options:

- Special sleeve block kits are available for all models (max. 980 kg). They enable doubling the capacity half the working speed
- Extension power supply and control cable per m.
- Radio remote control
- Wire rope 10-100 m in 10 m. length interval. Other lengths on request
- Do only use original Minifor steel wire rope
- Metal storage box
- Wire rope reeler
- Alternatively with cable reeling device (max. 40 m), wireless remote control, set of sheave blocks

Marking: CE-marked, Load capacity, serial number.

Note: Excl. wire (to be ordered separately).

Part code	WLL (metric) tonnes	Lifting speed m/min	Type	WLL sheaved ton	Speed sheaved m/min	A in	B in	C in	D, in	E in	F in	G, in	H, in	Imm in	J in	K in	L in	Mmm in	Weight lb
540642789	0.1	15	TR10	0,2	7,5	16.81	0.79	5.51	24.84	8.23	4.41	0.79	0.79	12.76	14.02	4.49	0.59	-	44.09
540642889	0.3	5	TR30	0,6	2,5	16.81	0.79	5.51	24.84	8.23	4.41	0.79	0.79	12.76	14.02	4.49	0.59	-	44.09
540642989	0.3	13	TR30S	0,6	6,5	16.93	0.79	8.35	25.28	14.37	8.82	7.64	3.54	0.79	0.79	13.66	19.37	11.89	72.75
540644849	0.5	7	TR50	0,95	3,5	16.93	0.79	8.35	25.28	14.37	8.82	7.64	3.54	0.79	0.79	13.66	19.37	11.89	72.75

Technical data

Type	Dimensions	Power supply*	Wire rope reeler	Radio
	LxWxD mm	Single phase	Single phase	3 phase
		20 m	27 m	40 m
		control		
115 Volt	230 Volt	400 Volt		
TR10	355x420x180	•	•	•
	•	•	•	•
TR30	355x420x180	•	•	•
	•	•		

Blueprint

