

Eye Foundry Hook X-047

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Testing according to DIN PAS 1061 and ASTM A952/A 952M.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Designed for the assembly of chain slings where wide throat openings are necessary

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
[... Read more](#)

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Standard: EN 1677-1


Warning: Before using the hook, check whether hooks without safety latches are allowed to be used for the particular application.

Safety factor: 4:1

Grade: 10

Eye Foundry Hook X-047

Blueprint



Technical data

Part code	Chain diameter in	WLL lb	EWL mm	A in	D in	H, in	K in	Pmm in	T in	Weight lb
402300250800	1/4-5/16	5,700	123	0.94	0.47	1.18	4.84	2.44	0.75	1.76
402300400800	3/8	8,800	149	1.26	0.59	1.38	5.87	2.91	0.91	3.53
402300670800	1/2	15,000	180	1.57	0.75	1.54	7.09	3.46	1.26	5.73
402301000800	5/8	22,600	213	1.97	0.98	1.81	8.39	3.86	1.61	9.92
402301600800	3/4	35,300	248	2.36	1.02	2.32	9.76	4.45	2.28	20.5
402300140800	-	-	93	0.71	0.24	0.87	3.66	1.89	0.67	0.73