Industrial Rigging & Supply | Lifting Solutions Group
Axel Johnson International

Half Coupling Link 8-054

Product information



- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- To combine with 8-088N Insulated Blank Swivel

... *Read more*

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard
Temperature range: Tempering temperature minimum 400°C
Standard: EN 1677-1

Safety factor: 4:1
Grade: 8

© November 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Half Coupling Link 8-054

Blueprint



Technical data

Part code	Chain diameter mm	WLL (metric) tonnes	A in	D in	K in	L in	Weight lb
401200110140	6	1.12	0.59	0.28	0.67	0.87	0.22
401200200140	7-8	2	0.71	0.35	0.87	1.1	0.22
401200320140	10	3.15	0.98	0.43	1.02	1.34	0.44
401200530140	13	5.3	1.18	0.63	1.38	1.77	0.88
401200800140	16	8	1.42	0.75	1.5	1.97	1.32
401201250140	18-20	12.5	1.65	0.87	1.81	2.36	2.43
401201500140	22	15	1.93	0.94	2.32	2.99	3.75
401202120140	26	21.2	2.17	1.18	2.44	3.15	5.95
401203150140	32	31.5	2.72	1.42	3.11	3.94	11.02

© November 2026 - All Rights Reserved