

Clevis Masterlink X-059

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... [Read more](#)

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.


Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Clevis Masterlink X-059

Blueprint



Technical data

Part code	Chain diameter in	WLL lb	EWL mm	A in	G, in	H, in	K in	L in	T in	Weight lb
402100250510	1/4-5/16	5,700	99	0.39	2.56	0.59	4.06	3.27	0.75	0.88
402100400510	3/8	8,800	125	0.43	3.78	0.75	5.24	4.25	0.75	1.76
402100670510	1/2	15,000	168	0.55	4.25	0.87	6.61	5.35	0.98	3.31
402101000510	5/8	22,600	198	0.71	4.88	1.02	7.99	6.5	1.06	5.29