

Eye Sling Hook X-044/S

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2,5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

... [Read more](#)

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.


Standard: EN 1677-2

Safety factor: 4:1

Grade: 10

Eye Sling Hook X-044/S

Blueprint



Technical data

Part code	Chain diameter in	WLL	A in	D, in	H, in	K in	P1 mm in	T in	Weight lb
402300140010	7/32	3,200	0.79	0.39	0.75	3.15	0.91	0.67	0.66
402300250010	1/4-5/16	5,700	0.98	0.47	0.87	3.86	1.1	0.79	1.1
402300400010	3/8	8,800	1.3	0.59	1.18	4.8	1.42	0.91	2.2
402300670010	1/2	15,000	1.57	0.71	1.5	5.98	1.57	1.1	3.97
402301000010	5/8	22,600	2.01	0.87	1.73	7.28	1.73	1.42	7.5
402301600010	3/4	35,300	2.4	1.06	2.52	9.06	2.13	1.89	16.09
402301900010	7/8	42,700	2.01	1.22	2.4	9.65	2.99	2.05	20.5
402302650010	1	59,700	2.56	1.34	3.03	11.22	3.03	2.4	29.76
402304000010	1-1/4	90,400	3.58	1.61	3.11	14.09	4.49	2.56	48.5