Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Web Sling Connector X-016

Product information



At least 25% greater WLL than traditional Grade 8 products.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Tempering temperature minimum 400°C

... *Read more*

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, Type, manufacturer ID, traceability.
Temperature range: -40° up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-1

Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Web Sling Connector X-016

Blueprint



Technical data

Part code	Chain diameter in	WLL lb	EWL mm	A in	B in	D in	K in	W in	Weight lb
402200140200	7/32	3,200	55	0.59	0.67	0.28	2.2	1.54	0.44
402200250200	1/4-5/16	5,700	62	0.71	0.91	0.35	2.48	1.54	0.66
402200400200	3/8	8,800	78	0.98	1.06	0.43	3.03	1.81	1.32
402200670200	1/2	15,000	95	1.18	1.46	0.63	3.82	2.09	2.43
402201000200	5/8	22,600	115	1.42	1.54	0.75	4.49	2.6	4.41
402201600200	3/4	35,300	132	1.65	1.81	0.87	5.2	3.11	7.05
402201900200	7/8	42,700	187	1.93	2.32	0.94	7.4	4.88	16.98

© November 2026 - All Rights Reserved