

Swivel Self Locking Hook Cartec CRGX

Product information



Swivel self-locking hook CRGX designed for grade 100 lifting applications. Equipped with a 360° swivel and an automatic locking mechanism that engages under load, ensuring secure lifting and preventing accidental release. The swivel feature allows rotation to reduce chain twist and improve load positioning during operations. Built from high-strength alloy steel for durability and reliability in heavy-duty environments such as construction, industrial rigging, and material handling.

... [Read more](#)

Material: Alloy steel

Marking: CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL


Finish: Powder coated

Safety factor: 4:1

Grade: 10

Swivel Self Locking Hook Cartec CRGX

Blueprint



Technical data

Part code	Chain diameter in	WLL lb	Rmm in	A in	B in	Omm in	D in	G, in	H, in	T in	Weight lb
402300142350	1/4	3,000	6.3	1.1	1.06	1.42	0.51	0.63	0.83	1.38	1.32
402300252350	9/32-5/16	5,700	7.17	1.34	1.06	1.42	0.51	0.79	1.02	1.69	2.43
402300402350	3/8	8,800	8.54	1.77	1.38	1.77	0.63	0.98	1.18	2.2	4.41
402300672350	1/2	15,000	10.67	2.13	1.77	1.97	0.83	1.38	1.57	2.72	8.82
402301002350	5/8	22,600	12.6	2.44	2.28	2.44	0.94	1.5	1.97	3.15	14.99