

Air Chain Hoists Red Rooster TMH-series (3.000 - 15.000 kg)

Product information



With M4 classification of mechanism this hoist is extremely reliable. This hoist will guarantee the continuity of your process. The TMH hoists are designed with a full load supporting eye for installation and securing (during lift applications) the hoist for extra safety.

Standard features:

- Precise variable speed control (cord- and pendant control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (80 dBA)
- Air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

Optional features:

- Marine Specification/Corrosion resistant
- Paint systems from C2 - Industrial to C5 - Offshore specification (Red finish as standard. Other RAL colours available on request)
- Choice of pendants
- Radio control pendant for electro pneumatic controls
- Control systems
- Chain collectors (PVC, galvanised or stainless steel)
- Various types of hook or clevis available
- Air supply systems and valves


... [Read more](#)

Marking: According to standard, CE-marked

Standard: EN 14492-2

Air Chain Hoists Red Rooster TMH-series (3.000 - 15.000 kg)

Blueprint



Technical data

Part code	Code	WLL (metric tonnes)	Number of falls	Lifting speed without load m/min	Air consumption lifting (l/sec)	Lifting speed with load m/min	Lowering speed with load m/min	Air consumption lowering (l/sec)	A in	B in	C in	D, in	E in	F in	H Ø in	Imm in	Weight lb
5601TMH3000C	TMH-3000C	3	1	10.8	56	5.4	10.2	68	21.14	12.36	7.44	4.92	10.43	12.24	1.97	1.34	218.26
5601TMH3000PE	TMH-3000PE	3	1	10.8	56	5.4	10.2	68	21.14	12.36	7.44	4.92	10.43	12.24	-	-	218.26
5601TMH6000C2	TMH-6000C2	6	2	5.4	56	2.7	5.1	68	29.21	14.61	9.65	4.96	10.43	12.24	2.56	1.65	273.37
5601TMH6000P2E	TMH-6000P2E	6	2	5.4	56	2.7	5.1	68	29.21	14.61	9.65	4.96	10.43	12.24	2.56	1.65	273.37
5601TMH9000C3	TMH-9000C3	9	3	3.6	56	1.8	3.4	68	30.83	17.91	6.3	11.61	10.43	12.24	2.95	2.09	374.79
5601TMH9000P3E	TMH-9000P3E	9	3	3.6	56	1.8	3.4	68	30.83	17.91	6.3	15.55	10.43	12.24	2.95	2.09	374.79
5601TMH12000C4	TMH-12000C4	12	4	2.7	56	1.35	2.5	68	33.7	15.69	5.89	9.8	12.17	10.47	3.27	2.52	418.88
5601TMH12000P4E	TMH-12000P4E	12	4	2.7	56	1.35	2.5	68	33.7	15.69	5.89	9.8	12.17	10.47	3.27	2.52	418.88
5601TMH15000C5	TMH-15000C5	15	5	2.16	56	1.08	2.04	68	33.66	18.35	6	12.34	11.81	10.83	3.27	2.28	617.29
5601TMH15000P5E	TMH-15000P5E	15	5	2.16	56	1.08	2.04	68	33.66	18.35	6	12.34	11.81	10.83	3.31	2.28	617.29