Industrial Rigging & Supply | Lifting Solutions Group
Axel Johnson International

Sling Connector S-238

Product information



High Performance Sling Connector is designed to connect to slings of all materials.

Features:

- Allows easy connection to master links or eye hooks and is ideal for bridles.
- Increased radius of bow gives wider sling bearing surface resulting in an increased area for load distribution, allows better load distribution on internal fibers.
- Increases synthetic sling efficiency as compared to master links, shackle bows and conventional eye hooks. This allows 100% of the sling's rated Working Load Limit to be achieved.

... *Read more*

Material: Alloy steel
Marking: Size, Logo, Product Identification Code (PIC)

Safety factor: 5:1

Industrial Rigging & Supply
info@industrialrigging.ca
+1 (519) 624-9697

© November 2026 - All Rights Reserved

Industrial Rigging & Supply | Lifting Solutions Group Axel Johnson International

Sling Connector S-238

Blueprint



Technical data

Part code	WLL lb	Size	Webbing width in	A in	B in	C in	E in	G in	H in	K in	M in	W in	Weight lb
402200230460	5,000	5	2	0.88	1.42	2	3.18	1	0.8	4.88	3.3	1.38	1.61
402200450460	10,000	10	3	1.42	1.52	2.75	4.13	1.25	0.98	5.71	3.76	1.75	3.31
402200680460	15,000	15	3	1.63	1.58	2.75	4.37	1.38	1.1	6.14	3.98	1.88	4.89
402201130460	25,000	25	4	2	2.33	3.75	5.98	1.75	1.41	8.39	5.59	2.25	10.1
402201360460	30,000	30	4	2	2.2	3.75	6.18	1.75	1.41	8.15	5.31	2.38	11.4
402201810460	40,000	40	5	2.25	2.91	4.76	7.24	2.25	1.78	10.47	6.93	3.09	20.7
402202720460	60,000	60	6	2.56	3.36	5.75	9.13	2.31	1.86	11.73	7.99	3.16	31.97

© November 2026 - All Rights Reserved