



Sling Connector S-238

Product information

High Performance Sling Connector is designed to connect to slings of all materials.

Features:

- Allows easy connection to master links or eye hooks and is ideal for bridles.
- Increased radius of bow gives wider sling bearing surface resulting in an increased area for load distribution, allows better load distribution on internal fibers.
- Increases synthetic sling efficiency as compared to master links, shackle bows and conventional eye hooks. This allows 100% of the sling's rated Working Load Limit to be achieved.

Safety factor: 5:1

Part code	WLL lb	WLL (metric) tonnes	Size	Webbing width in	A mm	B mm	C mm	E mm	G mm	H mm	K mm	M mm	W mm	Weight kg
402200230460	5,000	2.268	5	2	22.4	36.1	50.8	80.8	25.4	20.3	124	83.8	35.1	0.73
402200450460	10,000	4.536	10	3	36.1	38.6	69.9	105	31.8	24.9	145	95.5	44.5	1.5
402200680460	15,000	6.804	15	3	41.4	40.1	69.9	111	35.1	27.9	156	101	47.8	2.22
402201130460	25,000	11.34	25	4	50.8	59.2	95.3	152	44.5	35.8	213	142	57.2	4.58
402201360460	30,000	13.608	30	4	50.8	55.9	95.3	157	44.5	35.8	207	135	60.5	5.17
402201810460	40,000	18.144	40	5	57.2	73.9	121	184	57.2	45.2	266	176	78.5	9.39
402202720460	60,000	27.216	60	6	65	85.3	146	232	58.7	47.2	298	203	80.3	14.5

Blueprint

