

Transport chain is considered the chain of choice for load binding applications. It is also well suited for tie-downs, towing and logging operations. Its strength to weight ratio exceeds that of Proof Coil and High Test. Transport chain meets Department of Transportation regulations.

NOT FOR OVERHEAD LIFTING.

Full Drum (4 to 1 D.F.)



Trade Size		Wire Dia. (Inches)	Inside Link Dim. (Inches)		Ft. Per Drum	Net Wt. (Lbs.)	Working Load Limit	
Inches	MM		Length (Nominal)	Width (Min.)			Lbs.	Kgs.
1/4	7	0.274	1.236	0.480	800	508	3,150	1,429
5/16	8	0.334	1.120	0.480	550	550	4,700	2,132
3/8	10	0.392	1.374	0.551	400	544	6,600	2,994
1/2	13	0.510	1.782	0.750	200	460	11,300	5,127
5/8	16	0.625	2.016	0.851	150	521	15,800	7,166

**Made to Short Link specs*

Half Drum (4 to 1 D.F.)



Trade Size		Wire Dia. (Inches)	Inside Link Dim. (Inches)		Ft. Per Drum	Net Wt. (Lbs.)	Working Load Limit	
Inches	MM		Length (Nominal)	Width (Min.)			Lbs.	Kgs.
1/4	7	0	1.236	0.480	400	254	3,150	1,429
5/16	8	0.334	1.120	0.480	275	275	4,700	2,132
3/8	10	0.392	1.374	0.551	200	272	6,600	2,994
1/2	13	0.510	1.782	0.750	100	230	11,300	5,127
5/8	16	0.625	2.016	0.851	75	261	15,800	7,166

**Made to Short Link specs*

All G70 domestic chain (5/16, 3/8, 1/2) is stamped with the Working Load Limit every 10 links as shown.



Do not exceed Working Load Limits (WLL)!
See the SAFETY GUIDELINES section before using these products.



Industrial Rigging & Supply

E-mail info@industrialrigging.ca Website - www.industrialrigging.ca Toll Free (866) 942-4774