

CM Series 640 Long Handle Lever Puller



The CM Series 640 Long Handle Lever Puller is designed for heavy-duty construction and industrial applications. Used to pull, lift, drag or stretch, it features:

- Tough aluminum alloy construction and powder coat finish
- Weatherproof for outdoor service
- Simple construction with fewer parts for ease of maintenance and lower inventories
- Hoistalloy hardened steel link type load chain for strength, long wear life and flexibility
- Weatherized Weston-type automatic braking system for positive load control
- Easy, one-hand operation and control only 58 pounds of pull required for 3/4 tonne model capacity
- Forged upper and lower hooks with latches standard
- Free wheeling for fast and easy attachment to load
- Upper and lower Latchlok hooks available for all capacities
- Optional Load Limiter protection device stops transmission of lever forces protecting against dangerous overload
- Optional anchor sling simplifies attachment to allow anchor hook to swivel in tight space applications (3/4 & 1-1/2 tonne units only)
- Optional Load Sentry warns of overload condition
- Optional zinc-plated chain available
- Unlimited lift
- Lifetime warranty
- Metric rated
- Made in U.S.A.




Puller specifications - standard unit

Rated capacity* (tons)	Product code	Standard lift† (ft.)	Pull to lift full loads (lbs.)	Minimum distance between hooks (in.)	Lever length (in.)	Reeving	Hook throat openings (in.)	Approx. shipping weight (lbs.)
3/4	4043	5	58	10 ³ / ₄	21 ¹ / ₄	1	1 ¹ / ₃₂	16
1 ¹ / ₂	4045	5	89	14 ¹ / ₄	21 ¹ / ₄	1	1 ¹ / ₈	26
3	4047	5	95	16 ¹⁵ / ₁₆	21 ¹ / ₄	2	1 ⁷ / ₃₂	38
6	4050	5	96	21 ³ / ₈	21 ¹ / ₄	4	1 ³ / ₄	73

† Can be supplied with lifts longer than 5 feet



Optional anchor sling
(3/4 and 1¹/₂ tonne)



Latchlok type hook



Optional kits

Rated capacity* (tons)	Load Limiter		Load Sentry kit			Anchor sling kit	
	Product code	Approx. shipping weight (lbs.)	Product code	Lever length (in.)	Approx. shipping weight (lbs.)	Product code	Approx. shipping weight (lbs.)
3/4	4190	8 ¹ / ₄	4096	23 ³ / ₄	4 ¹ / ₂	4071	2
1 ¹ / ₂	4191	8 ¹ / ₄	4098	23 ³ / ₄	4 ¹ / ₂	4072	4 ³ / ₄
3	4191	8 ¹ / ₄	4098	23 ³ / ₄	4 ¹ / ₂	—	—
6	4191	8 ¹ / ₄	4098	23 ³ / ₄	4 ¹ / ₂	—	—

*** ⚠ WARNING**

Overloading and improper use can result in injury.

To avoid injury:

- Do not exceed working load limit, load rating capacity
- Do not use to lift people or loads over people.
- Use only alloy chain for overhead lifting.
- Read and follow all instructions.G



Industrial Rigging & Supply

E-mail info@industrialrigging.ca Website - www.industrialrigging.ca Toll Free (866) 942-4774